



Offer 374488

BAUMANN NUP 1000 from 2006

Pile Lifts



Offer Details

Offer Number:	374488
Brand:	BAUMANN
Model:	NUP 1000
Manufacturer	BAUMANN
Condition:	Good
Year:	2006
Incoterm:	Load On Truck
Cylinders Condition:	
Under Power:	No
Still in production:	No
Test possible:	No
Complete and in working condition:	Yes
Availability:	In stock
Counter:	
Machine number:	
Description:	with platform, suitable for all guillotines up to 115 cm<>on casters, <>with hydraulic control, double chain, touch control, safe stop above ground<>with photo-electrical cell control for the rise and descent

Technical details

Max. size	1000x1400 mm
HS Code	84439959 HS Codes Classification of Other

PRICE: Upon request

Images



	NU 650 1	NU 1000 1	NUP 650	NUP 1000	NUP 1600	NU 3000
fourches	6500 (ca. 650 kp)	10000 (ca. 1000 kp)	6500 (ca. 650 kp)	10000 (ca. 1000 kp)	16000 (ca. 1600 kp)	16000 (ca. 1600 kp)
fourches max. [mm]	440 - 780	440 - 780	—	—	—	—
fourches max. [mm]	800 x 1100	1000 x 1150	—	—	—	—
fourches min. [mm]	—	—	800 x 1100	1000 x 1150	1200 x 1475	1300 x 1600

Environnement	Transport et Stockage	Opération
température	-25 °C jusqu'à +55 °C sec, couvert d'un tissu	+15 °C jusqu'à +50 °C sec, couvert d'un tissu
humidité	Veillez observer les indications de transport sur l'emballage, ne pas renverser, si possible exempt d'oscillation	exempt de poussière, sans poussière horizontale ou fine
bruit	< 70 dB (A)	

Il est équipé de fourches support réglables.

1 Dessin

Spécifications Techniques						
	NU 650 1	NU 1000 1	NUP 650	NUP 1000	NUP 1600	NU 3000
L x l x h [mm]	1360 x 1200 x 1450	1560 x 1300 x 1500	1400 x 1250 x 1450	1600 x 1550 x 1500	1650 x 1750 x 2000	2000 x 1750 x 2100
largeur [mm] L x l x h	2360 x 2200 x 1500	2560 x 2300 x 1600	2100 x 2150 x 1450	2600 x 3550 x 1600	2850 x 2750 x 1700	3050 x 2800 x 1700
hauteur [mm] L x l x h	1600 x 1500 x 1800	1800 x 1750 x 1900	1600 x 1500 x 1600	1910 x 1750 x 1900	2200 x 2000 x 2000	2200 x 2000 x 2000
largeur [mm] L x l x h	400	500	410	510	610	810
hauteur [mm] L x l x h	520	650	550	680	890	1180
	NU 650 1	NU 1000 1	NUP 650	NUP 1000	NUP 1600	NU 3000
			230/400 V 3N~ 50 Hz			
puissance [kW]	5 A 2,5 kVA	6 A 2,5 kVA	5 A 2,5 kVA	5 A 2,5 kVA	7 A 3,5 kVA	11 A 5,5 kVA

Il est équipé de fourches support réglables.
Le déplacement nécessaire à droite et à gauche, ainsi que devant et derrière la machine, est 0,5 m et peut varier.



