



Offer 380772

BOBST SP 102-BMA from 1987

Die Cutter (Flatbed)

Offer Details

Offer Number	380772
Brand	BOBST
Model	SP 102-BMA
Manufacturer	BOBST
Condition	Good
Year	1987
Incoterm	EX Works
Cylinders Condition	
Under Power	Yes
Still in production	Yes
Test possible	Yes
Complete and in working condition	Yes
Availability	
Counter	
Machine number	

Description	* overhauled in 2009 FEEDER Universal non-stop feeder In line pile preparation Suction unit with multiple adjustments FEED TABLE 4 Front lays, adjustable in pairs with front register control Pull guide (OS) Transport belts PLATEN Heated upper head with 16 independent heating zones Steel stamping supporting plate Thickness: 21.5 mm 2 x Honeycomb chase (E-6) for 6,35 or 7 mm dies 2 x Stamping plate, BM (E-62) Thickness: 2,3 mm Compensating plate, BM (E-52) Thickness: 3,0 mm Lateral guiding device for foil Motorized foil tension shaft control with air cooling Automatic "on and off" pressure device of the platen Blower for stabilizing the sheet before stamping or converting Blower for releasing the foil after stamping Device for manual introduction of foil Lateral foil removal system, combined with rotating brushes, with speed modulation in function with foil advance Device for lengthwise slitting of foil Foil break control system for 16 foils Removable foil supply module comprising 3 x individual motor-driven advance regulating shafts 2 x telescopic sliding rails for reel-holders 2 x reel-holder axles 2 x additional reel-holder used for off-machine preparation 3 x sets of 8 reel-holder levers with combinable 1" and 3" hubs, including: 1 set for narrow reels, 1 set for mid-sized reels, 1 set for large reel 15 narrow drive rollers, width 14 mm 15 wide drive rollers, width 38 mm 1 movable stand (OOS) for the installation or removal of the BMA device. DELIVERY Pile tray Adjustable rear and side jogger. Manual non-stop rack Options added: Die cutting chase E-1 Compensating plate E-3 Micrometric adjusting plate E-55 Set of thin cutting plates E-98 Compatible with SP 102 Evoline Technical data CONVERTIBLE STOCK Minimum paper range: 80 - 90 g/sqm Maximum cardboard range: 2000 g/sqm Maximum corrugated board thickness: 4 mm PILE HEIGHT Maximum height feeder(normal mode): 1820 mm Maximum height feeder(with pile preparation device): 1710 mm Maximum height Feeder(non-stop): 1660 mm Maximum height Feeder(with pile preparation device non-stop): 1550 mm Maximum height Delivery: 1460 mm Gripper margin: 9 - 17 mm Height of embossing dies: 6,35 / 7 mm Height of cutting rules: 23,8 mm PLATEN TEMPERATURE Adjustable temperature: 50 - 160 °C 16 x adjustable temperature zones FOIL SUPPLY MODULE Maximum reel diameter: 250 mm Foil web width: 25- 1010 mm 3 x advance shafts Maximum programmable advance: 720 mm
--------------------	---

Technical details

Sheet size max	720x1020 mm
Sheet size min.	350x400 mm
Embossing size max.	680x1010 mm
Stamping size max.	680x1010 mm
Gripper margin	705x1020 mm
Platen pressure max.	250 t
Production speed	7.500 cycles/h. (foiling and embossing)
HS Code	84439959 HS Codes Classification of Other

PRICE: Upon request

Images



