



Offer 382204

CMC SMART MAILER from 2022

Inserting Machines

Offer Details

Offer Number	382204
Brand	CMC
Model	Smart Mailer
Manufacturer	CMC
Condition	Good
Year	2022
Incoterm	
Cylinders Condition	
Under Power	Yes
Still in production	Yes
Test possible	Yes
Complete and in working condition	Yes
Availability	
Counter	
Machine number	

Description

Counter: 13 mil.imps.
The CMC SMART MAILER is a compact continuous motion inserter which allows running a wide range of products.
Thanks to its modular configuration, CMC SMART MAILER can be customized to a wide range of products granting the highest integrity of data during the enveloping process with real-time product tracking controls, barcodes matching through optical readers or cameras, in line printing, selective feeding according to the barcode coming from a database, final daily report of all product runs sent to a company network system.
All adjustments are fast and easy, ensuring correct and quick setting.
The machine is equipped with a by-pass for the automatic rejection of wrong envelopes.

N° 2 A15
Electronic hopper feeder for feeding rigid and thick products in-line, suitable for stitched products and bound booklets.
Product length: from 120 to 320 mm
Product width: from 100 to 300 mm
Min. thickness: 1 mm
Max. thickness: 25 mm

N° 3 A21F
Thickness gauge controlled by photocell.

N° 3 A14Q
Technical specifications:
Product length (L): 100 to 210 mm
Product width (W): 110 to 300 mm
Product thickness:
min.: 1 sheet 70gr/sqm
max.: 4 mm
Min paper grammage:
70 gr/sqm

N° 1 SEP1
Rotary disk separator for sheet feeder.

N° 1 F15
Very high speed sheet feeder.
The system consists of a feeding drawer with a loading capacity as high as 500 sheets.
Sheets are drawn by special toothed belts.
The document thickness can be adjusted by means of a dedicated handwheel.
An electronic sensor detects possible double feeds.
This can be calibrated by simply passing a sheet under the sensors.
The feeder is driven by a Brushless motor.

Technical specifications:
Minimum Format: 80x110 mm
Maximum format: 210x300 mm
Minimum paper grammage: 70 gr./Sqm
Maximum thickness: 2 mm
Special guides for small stickers.

N° 1 A14_Env_L
Large envelope feeder

N° 1 VACUUM BELT
N° 1 HMI
Automatic programmable hot-melt gluing system, equipped with 1 glue-gun.

N° 1 RA20_i
Conveyor for collation of staggered products.

N° 1 PC_Add Special
This software has the following functions:
Printing checking
Checking of printed labels by means of bar-code reading
Data pre-processing
Database import from Access-MDB or not-standard formats (variable length, set of character transcoding, etc)
Barcode Management
Possibility of managing up to 10 barcode readers or cameras simultaneously, by displaying the percentage in reading, etc
Thermal printer management
PC_ADD is capable of managing the most common thermal printers for over-bundle labels (Zebra, Sato, Intermec, Novex, KoalaBar, etc).

Technical details

Max format:	210x300 mm
Min format	80x110 mm
Mech. speed	4.000 e/h
HS Code	84439959 HS Codes Classification of Other

PRICE: Upon request

Images



