



Offer 383568

MK MK 1050 YMI-II from 2006

Die Cutting+Embossing+Foil Stamping

Offer Details

Offer Number	383568
Brand	MK
Model	MK 1050 YMI-II
Manufacturer	MK
Condition	Good
Year	2006
Incoterm	
Cylinders Condition	
Under Power	Yes
Still in production	Yes
Test possible	Yes
Complete and in working condition	Yes
Availability	Immediately
Counter	
Machine number	

Description	Continuous automatic feeding with pre-loading; • High-speed automatic feeding with a maximum speed of 108 sheets per minute; Four pneumatic suction cups, adjustable for height and angle; • Three electronic safety sensors prevent the platen from being raised excessively; • Side air-blow system to enhance sheet separation; Double-sheet detector; • Four front rollers: two fixed and two movable, controlled by a worm drive for different paper formats; Automatic emergency stop system in the event of a sheet jam; Separate drives for the automatic feeder section and the entire machine facilitate easy set-up; LCD display and camera for controlling the machine's synchronisation; Four brush rollers for thin paper; 10 distribution blades for thick cardboard; • 30 distribution blades for thin paper; Fine-tuning of the cutting force via a servo motor worm drive; • Axial shaft made of 40Cr steel; • Upper and support plates made of QT60 malleable cast iron; • Precise positioning of the closing frame, ensured by photoelectric sensors; • Closing frame rotation mechanism; • Gearbox cooling and lubrication system; • Overload protection device with a torque limiter ensures the highest level of safety during operation; • Universal frame – 1 pc; • Pneumatic pump manufactured by Becker (Germany) – 1 pc; • Plates: 5.00 mm – 1 pc., 3.00 mm – 1 pc. and 1.5 mm – 4 pcs.; • Pneumatic clamping and release mechanism for the end frame; • Chain pulling mechanism (UK); • Patented instantaneous mechanism Hot foil stamping section • 4 individually controlled foil rollers, servo-driven; • 20 individually controlled heating zones with a tolerance of +/-5 °C; • Patented foil tension control device, ensuring a stamping accuracy of +/-0.2 mm; • 9 electronic foil breakage sensors; • Computer with an industrial-grade LCD monitor; • Information displayed on the LCD monitor regarding the foil feed position (in English); • One software package (in English); • 1 honeycomb frame with 160 clamps for securing the printing plate. Delivery section • Continuous receiving system with two wooden stops; • Safety photoelectric sensors prevent the paper pile from becoming overfilled or underfilled at the delivery section; • Production counter; • Brushes with adjustable angles
--------------------	--

Technical details

Sheet size max.	1050x750 mm
Min. sheet size	400x350 mm
Diecutting size	1040x740 mm
Platen pressure max.	2.5MN
Production speed	5.000 SPH
Gripper margin	9~17mm
Thickness range	0.1
HS Code	84439959 HS Codes Classification of Other

PRICE: Upon request