Offer 377735

ROTATEK FX FX4 COMBI from 2004

Uv Flexo

Offer Details

Offer Number	377735
Brand	ROTATEK
Model	FX FX4 Combi
Manufacturer	ROTATEK
Condition	Good
Year	2004
Incoterm	EX Works
Cylinders Condition	
Under Power	Yes
Still in production	Yes
Test possible	Yes
Complete and in working condition	Yes
Availability	
Counter	
Machine number	

Description	Equipment of this Labelprinter - Standard unwinding with 76 mm tension axis - Web edge control - Six offset printing units with ink mist extraction - Format slots 13", 18", 20" and 24" Max web width: 400 mm Max printing width: 390 mm Max speed: 150 m / min. Material thickness: 40 - 300 my Blankets: 0.95 mm self-adhesive - A flexographic printing unit - Laminating and cold foil station - Further processing with a punching machine and grid extraction - Winder with a tension axis 76 mm - completion, web cleaning - UV system Dr. Höhnle with a total of eight lamps, built in 2021 - Good general condition - rota punching, Rewind - Fountain solution: Techno Trans - Space: about 18 m x 5 m PART of the delivery are also: Plate bender and plate punch, each format set includes six offset cassettes, a flexo plate cylinder and a magnetic cylinder The Combi offset rotary press with variable format combines in line the advantages of offset and flexo printing, allowing any type of composition according to the client, with the combination of various printing elements (Offset, Flexo, Serigraphy, gravure etc.), processing (die cutting, hot and cold stamping, embossing) and finish (web, sheeter, etc.). There are no limits to the configuration of the Combi rotary press narrow web, be it for the production of any type of labels, covers, flexible films and other products requiring a complex printing process. Basic Configuration · Machine voltage: 400V, 50 Hz, triphasic + N + TT. · Electric equipment: · Preset counter/speed marker. · Centralized lubrication. · Machine equipped with safety standards CE · Mechanical transmission: · Motorized longitudinal register. · Operator panel with touch screen. · Coated guide rollers. · Protection of electrical equipment for voltage surges/drops. Unwinding Unit · Hydraulic roll lift. · One expandable air shaft 76 mm. · Maximum diameters of paper roll 000 mm. · Side displacement of the roll during operation of the machine +/- 7.5 mm. · Pneumatic brake through dancer roller. · End of roll by acoustic alarm and stop. · Web splice device. · Web guide device. Rotary Offset Printing Units · Individual main control panel. · Rotamoll dampening system for UV inks. · Third form roller. · Battery reinforcement. · Dampening system proportional to speed of machine. · Horizontal webbing. · Electronic taker. · Battery pneumatic disengage. · Ink agitator. Rotary Flexographic Unit · Individual main control panel. · Pneumatic fixing of printing cylinders. · Open inkpot. · Anilox cylinder to be defined. · Rotary printing cylinder format, as above Cold Stamping Unit

PRICE: Upon request